



## AB-364

|         |            |
|---------|------------|
| GRADE   | Industrial |
| FINISH  | Smooth     |
| POWDER  | Yes        |
| TRIMMED | Yes        |
| COLOR   | Black      |

## TECHNICAL SPECIFICATIONS

SPECIFICATION ASTM D2000: 1BE610

POLYMER: NITRILE BLEND (NBR/SBR)

| ASTM                                  | DESCRIPTION                                      | VALUE                                                                  |
|---------------------------------------|--------------------------------------------------|------------------------------------------------------------------------|
|                                       | SPECIFIC GRAVITY (gr/cc)                         | 1.34                                                                   |
| D2240                                 | HARDNESS (shore A)                               | 60                                                                     |
| D412                                  | TENSILE (psi)                                    | 1000 min.                                                              |
|                                       | ULTIMATE ELONGATION (%)                          | 350 min.                                                               |
| D395<br>(Method B)                    | COMPRESSION SET<br>22 hrs @ 100°C (212°F)        | 40% max.                                                               |
| D573                                  | HEAT AGING<br>70 hrs @ 100°C (212°F)             | Hardness: +/-15<br>Tensile (%): +/-30 max.<br>Elongation (%): -50 max. |
| D471                                  | OIL RESISTANCE<br>Oil #3, 70 hrs @ 100°C (212°F) | 80% max.                                                               |
| TEMPERATURE RANGE (general guideline) |                                                  | -30° to 190°F<br>(-34° to 88°C)                                        |

**Maximum pieces per roll: 2****Minimum piece length: 10'****Width tolerance: -0 / +1"****Material is within commercial sheet rubber gauge tolerances.**

The documentation for sheet rubber gauge tolerances is published on our website.  
Please ensure the product meets your application specification prior to order placement.  
Specifications are subject to change without notice. The website version prevails.



# AB-364

|                         | GAUGE<br>IN (MM) | WIDTH<br>IN (MM) | SURFACE/ROLL<br>SFT (M <sup>2</sup> ) | LENGTH/ROLL<br>LFT (M) | WEIGHT/ROLL<br>LBS (KG) |
|-------------------------|------------------|------------------|---------------------------------------|------------------------|-------------------------|
| 305-02-362 <sup>1</sup> | 1/32 (0.80)      | 36 (914.4)       | 600 (56.74)                           | 200 (60.96)            | 122 (55.3)              |
| 305-02-482              | 1/32 (0.80)      | 48 (1219.2)      | 800 (74.32)                           | 200 (60.96)            | 163 (73.9)              |
| 305-04-362 <sup>1</sup> | 1/16 (1.60)      | 36 (914.4)       | 300 (27.87)                           | 100 (30.48)            | 124 (56.2)              |
| 305-04-482              | 1/16 (1.60)      | 48 (1219.2)      | 400 (37.16)                           | 100 (30.48)            | 166 (75.3)              |
| 305-06-362 <sup>1</sup> | 3/32 (2.38)      | 36 (914.4)       | 225 (20.9)                            | 75 (22.85)             | 150 (68.0)              |
| 305-08-362              | 1/8 (3.20)       | 36 (914.4)       | 150 (13.93)                           | 50 (15.24)             | 138 (62.6)              |
| 305-08-482              | 1/8 (3.20)       | 48 (1219.2)      | 200 (18.58)                           | 50 (15.24)             | 184 (83.5)              |
| 305-12-362              | 3/16 (4.80)      | 36 (914.4)       | 120 (11.15)                           | 40 (12.19)             | 158 (71.6)              |
| 305-12-482              | 3/16 (4.80)      | 48 (1219.2)      | 160 (14.86)                           | 40 (12.19)             | 210 (95.3)              |
| 305-16-362              | 1/4 (6.35)       | 36 (914.4)       | 120 (11.15)                           | 40 (12.19)             | 210 (95.3)              |
| 305-16-482              | 1/4 (6.35)       | 48 (1219.2)      | 160 (14.86)                           | 40 (12.19)             | 279 (126.6)             |
| 305-24-362 <sup>1</sup> | 3/8 (9.50)       | 36 (914.4)       | 90 (8.36)                             | 30 (9.14)              | 233 (105.7)             |
| 305-24-482              | 3/8 (9.50)       | 48 (1219.2)      | 120 (11.15)                           | 30 (9.14)              | 311 (141.1)             |
| 305-32-362 <sup>1</sup> | 1/2 (12.70)      | 36 (914.4)       | 90 (8.36)                             | 30 (9.14)              | 314 (142.4)             |
| 305-32-482              | 1/2 (12.70)      | 48 (1219.2)      | 120 (11.15)                           | 30 (9.14)              | 418 (189.6)             |
| 305-40-362 <sup>1</sup> | 5/8 (15.90)      | 36 (914.4)       | 90 (8.36)                             | 30 (9.14)              | 390 (176.9)             |

<sup>1</sup> Made to order.